

Marked-up Specification

DIAGNOSIS SYSTEM FOR HOUSEHOLD ELECTRIC APPLIANCES

Cross-Reference To Related Applications

This is a U.S. national phase application under 35 U.S.C. §371 of International Patent Application No. PCT/BR2003/000185, filed December 2, 2003, and claims benefit of Brazilian Patent Application No. PI 0205470-1, filed December 5, 2002 both of which are incorporated by reference herein. The International Application was published in English on June 17, 2004 as WO 2004/051293 A1 under PCT Article 21(2).

Field of the Invention

The present invention refers to a diagnosis system for identifying the origin of failures in the operation of household electric appliances, such as refrigerators, freezers, air conditioners, and others, in which the operation of their different loads is defined by a command module mounted to the refrigeration appliance. The invention is particularly related to a diagnosis system incorporated to the household electric appliance and operatively associated with the command module.

Prior Art

In household electric appliances, particularly in the refrigeration appliances defined by refrigerators and freezers, in which there are provided different devices or loads, such as defrost resistances, fans, lamps, and compressor, the operation thereof is controlled by an electronic command module which is programmed to activate and deactivate the switches (generally relays) that energize the different loads of the appliance as a function of the desired operational conditions. In these appliances, the command module and the different electronic controls are energized by a generally DC power source, which in turn is energized by the power system that energizes the appliance.

The quick and reliable identification of the different failures in the operation of the above-mentioned appliances already installed in the residences of the users has been a constant preoccupation of the manufacturers.

When a failure in the operation of the appliance is noticed by the user and informed to the authorized technical assistance, it is the responsibility of the latter to identify the problem and solve it by repairing or replacing the damaged component. The deficiencies, whether caused by the operator or by the equipments and which usually appear during ~~the~~ a diagnosis phase[,] in which the prompt and reliable identification of the failure should be obtained, cause considerable losses to the manufacturer and to the users, as a function of improper replacements of the command module or of the different loads of the circuit of appliance, such as defrost resistances, fans, lamps, and compressor.

One of the systems presently used to reduce the time spent in the diagnosis and the errors made by the technicians comprises a diagnosis device developed to simulate the loads of each appliance model and which should be carried by the technician in charge, who will couple it to the command module of the appliance. The diagnosis device is then operated by the technician, according to a predetermined sequence of procedures to be followed, in such a way as to simulate the operational conditions of the involved loads and to check the conditions of the means that form the command module.

This known system type allows the technician in charge of the diagnosis to instruct the diagnosis device to execute each checking step, according to the predetermined sequence, and to observe visually the indications, generally luminous signs displayed in the diagnosis device and which represent the operational condition tested for each of the components (switches, etc.) of the command module, verifying whether a failure occurred in one of ~~said~~ the components and the real need for replacing it.

Nevertheless, this type of diagnosis system requires a skilled and careful operator to provide a reliable diagnosis, in order to avoid an undesirably high rate of diagnosis errors.

Another deficiency of the system mentioned above is due to the fact that it only indicates the operational conditions of the command module, requiring other test procedures to check the operational conditions of the different loads of the electric circuit of the appliance.

A further disadvantage of the solution that utilizes the diagnosis device is that the technician in charge needs to carry specific diagnosis devices for different appliance models. With an

undesirable high frequency, the checking of the damaged appliance is effected without the adequate diagnosis device, leading to unnecessary orders to replace the command module.

There are also known sophisticated solutions of self-diagnosis, which precisely indicate the defective component, such as those provided in some appliances, equipments, and devices.

- 5 However, these solutions of directly detecting the voltage values are relatively expensive, increasing the final cost of the appliance.

Objects of the Invention

- By reason of the deficiencies known heretofore, as discussed above, it is the generic object of the present invention to provide a diagnosis system to be incorporated into an electric
- 10 household appliance, such as a refrigerator, freezer, or air conditioner, in order to allow for a prompt, simple, and reliable identification of the operational failures, not only in the command module, but also in the loads energized thereby, without requiring the technician in charge to carry a special device to be coupled to the command module, or to base his conclusion on the interpretation of different test parameters to be observed and considered.
- 15 It is a further object of the invention to propose a diagnosis system incorporated to the appliance, such as mentioned above, which presents a simple construction of relatively low cost.

Summary of the Invention

- The present diagnosis system is directed to refrigeration appliances, such as refrigerators,
- 20 freezers, and air conditioners provided with loads, such as compressors, defrost resistances, lamps, etc., which are energized by switches commanded by respective electronic controls operatively coupled to a command module, which energizes the switches and an interface coupled thereto.

- According to a first aspect of the invention, the diagnosis system comprises: a voltmeter
- 25 operatively coupled to ~~the~~an inlet of each one of the loads, so as to measure a first voltage in the inlet of the loads with the switches opened, and a second voltage in the inlet of each load ~~with the~~having its respective switch closed; and a control unit operatively associated with the

5

10

15

20

25

The control unit 70 is operatively associated with both the command module 50 and the voltmeter 60 to define the operational sequence of closing and opening the switches 20 in the diagnosis procedure, and to record and process the voltage values informed by the voltmeter in the different operational conditions of the switches 20.

As illustrated in figure 2, the voltmeter 60 comprises a signal conditioning circuit 61, connected to the inlet of each load 10 upstream the respective switch 20 and supplying voltage signals from ~~said~~the inlet of the load 10 to an AD converter 62 connected to the control unit 70.

The signal conditioning circuit 61 is formed, in the illustrated example, by a resistive divider with “n” inlets corresponding to the quantity of loads to be diagnosed (in the present case, for example, three inlets), by a signal rectifying diode and a signal filtering capacitor, in order to adjust the inlet AC voltage to the levels required by the AD converter 62.

The signal conditioning circuit further comprises an assembly of resistors 63 respectively connected in parallel with the loads ~~10-70~~ for providing the adequate maintenance of a predetermined voltage in the circuit supplying the loads 10 upon opening thereof.

The voltage signals obtained from the inlet of the loads 10 are conditioned by the conditioning circuit and sent to the AD converter 62 and thence to the control unit 70.

The electronic control unit 10 and the command module 50 are operatively associated with an interface 80 that can take different forms, such as a connector for the acquisition or transfer of signals, a visual or sonorous alarm, or a display also mounted to the structure of the cabinet of the refrigeration appliance in a visible place and which can be further provided with activating means, such as keys, buttons, etc. (not illustrated), which allow the user to interact with the appliance, altering some operational parameters.

To initiate the diagnosis procedure, the technician de-energizes the refrigeration appliance and reconnects it subsequently, in order to activate, within a subsequent short period of time, generally not higher than 1 minute, the electronic control unit 70, with a predetermined password exclusively used by the technical assistance, giving start to an operational sequence of tests to be automatically performed by the control unit 70 with the aid of both the voltmeter 60 and the command module 50.

The electronic control unit 70 starts an operational phase of acquiring voltage values by means of the voltmeter 60. This phase of acquiring voltage values has the purpose of measuring, by means of the voltmeter 60, and recording, in the control unit 70, the voltage value V_{off} that supplies all the loads 10 in the de-energized (off) condition by opening the respective switches 20, and also the voltage values V_{res} , V_{lamp} , V_{comp} that supply each of the loads 10 in the energized (on) condition by closing ~~the~~ a respective switch 20, according to a predetermined sequence. Also in this phase of acquiring voltage values there can be further optionally obtained through the voltmeter 60 and recorded in the control unit 70 the supply voltage of each two or three loads 10 together, which can be simultaneously energized by closing the respective switches 20, as illustrated in figure 5.

In the exemplary operational sequence of tests illustrated in figure 4, the acquisition of the voltage values follows the steps below:

- opening all the switches 20;
- awaiting a certain minimum time to elapse, for example about 5 seconds, and measuring and recording a first voltage V_{off} corresponding to the voltage value in the inlet of all the loads 10, with the switches 20 opened;
- closing the switch 20 of the defrost resistance;

- awaiting the certain minimum time to elapse and measuring and recording the voltage value V_{res} in the inlet of the defrost resistance;
- opening the switch 20 of the defrost resistance;
- closing the switch 20 of the lamp;
- 5 - awaiting the certain minimum time to elapse and measuring and recording the voltage value V_{lamp} in the inlet of the lamp, whose switch 20 is closed;
- opening the switch 20 of the lamp;
- closing the switch 20 of the compressor;
- awaiting the certain minimum time to elapse and measuring and recording a second voltage
- 10 value V_{comp} in the inlet of the compressor, whose switch 20 is closed; and
- maintaining the switch of the compressor closed.

In case one desires to obtain voltage values in the inlet of each two or three loads 10 together, with their respective switches 20 being simultaneously closed, it is only necessary, before opening a switch 20 after acquiring the second voltage V_{res} , V_{lamp} , V_{comp} of the respective

15 load 10, to close another switch 20 and to measure and record the voltage value in the inlet of the two or three loads 10, whose switches are found simultaneously closed. It should be noted that the loads 10 to be associated for the joint measure of the voltage are those which can be simultaneously energized in the household electric appliance.

In the exemplary operational sequence of tests illustrated in figure 5, the acquisition of the

20 voltage values follows the steps below:

- opening all the switches 20;
- awaiting a certain minimum time to elapse, for example about 5 seconds, and measuring and recording a first voltage V_{off} corresponding to the voltage value in the inlet of all the loads 10, with the switches 20 opened;

- closing the switch 20 of the defrost resistance;
- awaiting the certain minimum time and measuring and recording the voltage value in the inlet of the defrost resistance;
- closing the switch 20 of the lamp;
- 5 - awaiting the certain minimum time and measuring and recording the voltage value V_{res_Vlamp} in the inlet of the defrost resistance and of the lamp;
- opening the switch 20 of the defrost resistance;
- awaiting the certain minimum time and measuring and recording a second voltage value V_{lamp} in the inlet of the lamp;
- 10 - closing the switch 20 of the compressor;
- awaiting the certain minimum time and measuring and recording the voltage value V_{res_Vcomp} in the inlet of the lamp and of the compressor;
- opening the switch 20 of the lamp;
- waiting for the certain minimum time and measuring and recording the voltage value V_{comp}
- 15 in the inlet of the compressor;
- maintaining the switch 20 of the compressor closed.

Once the voltage values in the inlet of the loads 10 have been recorded in the conditions in which the respective switches 20 are opened, closed, and optionally closed in different groups, the control unit 70 initiates a second processing phase, diagrammatically illustrated in figure 6

20 and which has the purpose of checking the operational conditions of the switches 20, of the electronic controls 30, and consequently of the plate of the command module 50 which also carries the electronic controls 30 and the switches 20.

According to figure 6, the phase of checking the plate of the command module 50 comprises the steps of comparing, sequentially, the first voltage V_{off} in the inlet of each of the loads 10

presenting the respective switches 20 in the open condition with the second voltages V_{res} , V_{lamp} , V_{comp} in the inlet of ~~said the~~ loads 10 presenting the respective switches 20 in the closed condition, and indicating, in the interface 80, whether the first voltage V_{off} is higher than the second voltage V_{res} , V_{lamp} , V_{comp} in the inlet of the respective load 10 with the switch closed. In case this condition occurs in all the loads 10, the processing system concludes that all respective switches 20 and the electronic controls 30 of the command module 50 are in good conditions, since no failures have been detected in the switches 20 or in their associated electronic controls 30.

In case in any of the steps of comparing the first V_{off} voltage with the second voltages V_{res} , V_{lamp} , V_{comp} of the loads 10 a different condition is detected in the relation of expected values, i.e., any second voltage with a value equal to or higher than that of the first voltage, the control unit 70 indicates the anomaly at the interface 80, informing the existence of a failure in one of the components of the plate of the command module 50, leading to the replacement of ~~said the~~ component. In this case, the diagnosis procedure is ended, since it is not safe to continue the tests of the loads 10 with the deficient command module 50. In the hypothesis the first voltage V_{off} is lower than the second voltages V_{res} , V_{lamp} , V_{comp} , the control unit 70 will produce in the interface 80 the indications that the problem is neither located in the command module 50 nor in its components defined by the switches 20 and respective electronic controls 30.

In figure 7 of the enclosed drawings, there is illustrated another construction for the operational sequence of checking the command module 50. In this construction, the checking of the plate of the command module 50 comprises a first step of defining a limit voltage V_{lim} lower than the first voltage V_{off} as a safety value. In a possible way of carrying out the invention, the limit value V_{lim} is approximately equal to 87.5% of the value of V_{off} .

Once the limit voltage value V_{lim} has been defined, the checking comprises the steps of comparing, sequentially, the second voltages V_{res} , V_{lamp} , V_{comp} in the inlet of the loads 10 having the respective switches 20 in the closed condition with ~~said the~~ limit voltage V_{lim} , and indicating in the interface 80 whether any of the second voltages V_{res} , V_{lamp} , V_{comp} is greater than the limit voltage V_{lim} .

In case this condition occurs in any of the loads 10, the processing system concludes that there is a failure in a component of the command module 50 operatively related to the load 10 and whose second voltage is greater than the limit voltage V_{lim} . In this case, the diagnosis procedure is not interrupted yet, differing from the procedure described in relation to the operational sequence illustrated in figure 6.

In the hypothesis of any second voltage V_{res} , V_{lamp} , V_{comp} being lower than or equal to the limit voltage V_{lim} , the control unit 70 may produce in the interface 80 the indications that the problem might not be located in the command module 50 and in its components defined by the switches 20 and respective electronic controls.

In the example of figure 7, there is provided an additional sequence for checking the command module 50, as illustrated in the lower half of the figure. According to ~~said~~ the operational sequence, a first processing step is provided, in which there is defined a first processing voltage V_{proc1} lower than the second voltage of a first load 10, which in the present example is represented by the second voltage V_{lamp} in the inlet of the lamp. In a way of carrying out the invention, the first processing voltage V_{proc1} corresponds to about 87.5% of the value of the second voltage V_{lamp} in the inlet of the first load, i.e., of the lamp. Subsequently, the following steps are processed by the control unit 70:

- checking whether the second voltage V_{comp} of a second load 10, for example the compressor, is lower than the first voltage V_{off} , whether the switch 20 of the first load 10 defined by the lamp is operative, and whether the second voltage $V_{lamp_V_{comp}}$ in the inlet of the second load 10, represented by the compressor, and of the first load 10, represented by the lamp, is lower than the first processing voltage V_{proc1} ;

- indicating, in the interface 80, by means of the control unit 70, whether the three conditions above have been fulfilled or not fulfilled, the last hypothesis leading to the indication that a problem exists in the switch 20 of the second load 10 represented by the compressor;

- checking whether the second voltage V_{res} of a third load 10 represented by the defrost resistance is lower than the first voltage V_{off} , whether the switch 20 of the first load 10 represented by the lamp is operative, and whether the second voltage $V_{res_V_{lamp}}$ in the inlet

of the third and of the first load 10, represented by the defrost resistance and by the lamp, is lower than the first processing voltage V_{proc1} ;

- indicating in the interface 80, by means of the control unit 70, whether the three conditions above have been fulfilled or not fulfilled, the last hypothesis leading to the indication that a

problem exists in the switch 20 of the third load 10, represented by the defrost resistance;

- recording, in the control unit 70, a second processing voltage V_{proc2} , about 12.5% lower than the second voltage V_{comp} of the second load 10, represented by the compressor;

- checking whether the second voltage V_{lamp} of the first load 10 represented by the lamp is lower than the first voltage V_{off} , whether the switch 20 of the second load 10 represented by the compressor is operative, and whether the second voltage V_{lamp_Vcomp} in the inlet of the second and of the first load 10, respectively represented by the compressor and the lamp, is lower than the second processing voltage V_{proc2} ;

- indicating in the interface 80, by means of the control unit 70, whether the three conditions above have been fulfilled or not fulfilled, the last hypothesis leading to the indication that a problem exists with the switch 20 of the first load 10, represented by the lamp.

This alternative processing illustrated in figure 7 allows checking more safely the operation of the command module 50, even considering substantial variations in the voltage supplied by the power system.

Upon completion of the checking operation of the command module 50, jointly with the switches 20 and the electronic controls 30, without finding any failure, the control unit 70 begins processing the sequence of tests of the different loads 10, according to one of two distinct operational sequences that will be automatically defined as a function of the results of a step of comparing the second voltages V_{res} , V_{lamp} , V_{comp} related to the loads 10 with the switches 20 in the closed condition.

In the hypothesis the second voltages of the different loads 10 are equal or substantially equal, the control unit 70 will initiate the test of the loads 10 by means of a first operational sequence

indicated in figure 3 and better illustrated in figure 7. In this first operational sequence, the control unit 70 verifies whether the first voltage V_{off} (switches opened) is higher than a certain reference voltage value V_{ref} , which in the example is 1.3V. In case this occurs, all the loads are considered to be in a good state, since the reference voltage V_{ref} illustrates a voltage value above which the first voltage V_{off} is compulsorily located with a certain margin of safety, in case the loads 10 are in adequate operational conditions.

Thus, in case a first voltage V_{off} (switches opened) is detected to be higher than the reference voltage V_{ref} , it can be concluded that all the loads are really correctly closed, i.e., in adequate operational conditions.

On the other hand, in case the control unit 70 detects a first voltage V_{off} that is equal to or lower than ~~said the~~ reference value, the interface 80 will be instructed to indicate that all the loads 10 are open. It should be noted herein that the present diagnosis system does not detect short circuits in the loads 10.

In the hypothesis the second voltages V_{res} , V_{lamp} , V_{comp} present differences of value, the control unit 70 will initiate the second operational sequence of load testing, as schematically illustrated in figure 9, with the purpose of identifying which load is open, and therefore, presenting a defect.

This second operational sequence of load tests comprises several steps, each basically comparing the second voltage V_{res} , V_{lamp} , V_{comp} of each load 10 (switch 20 closed) with a certain minimum voltage V_{min} , which may correspond, for example, to about 75% of the value of the lowest second voltage V_{res} , V_{lamp} , V_{comp} recorded in the voltage acquisition phase.

Thus, in case any second voltage V_{res} , V_{lamp} , V_{comp} measured in the inlet of a load 10 presents a value that is equal to or lower than that minimum value V_{min} , the control unit will send to the interface 80 an instruction identifying the open condition (failure) of ~~said the~~ load. In case a step of checking the operational condition of a load 10 concludes for the acceptance of the load, the control unit 70 will pass to the next step of checking the condition of another

load, with no need of indicating in the interface 80 whether this or that load is in acceptable conditions.

Upon completion of the steps of checking the condition of each of the loads 10, the control unit 70 instructs the command module 50 to normally operate the refrigeration appliance.

- 5 To carry out a new diagnosis procedure, the technician in charge may press a key in the appliance or disconnect the latter from the power system, awaiting a certain time until the compressor is activated, and then he reconnects the appliance and introduces in the command module 50, in the predetermined time, the specific password to initiate the diagnosis phases by instruction of the control unit 70.

ABSTRACT OF THE DISCLOSURE

A diagnosis system for household electric appliances, such as refrigerators, freezers, and others, presenting multiple loads, energized by switches commanded by electronic controls coupled to a command module, which energizes the loads and an interface. The system includes: a voltmeter to measure a first voltage (V_{off}) in the inlet of the loads with the switches opened and a second voltage in the inlet of each load with respective switch closed, and a control unit for processing the values of the first voltage and of each second voltage. The control unit provides and interface with an indication of a failure in the command module, in the switches, or in the respective electronic controls thereof, in case a second voltage presents a value that is equal to or higher than that of the first voltage.